

## Disabled Refuge EVC PRO OUTSTATION

### Braille Annotation Induction loop Photo luminescent

- Green photo luminescent fascia
- Braille and photo luminescent annotation
- Integral induction loop
- Adjustable audio output (up to 80dB)
- Suitable for standard and compact EVC systems
- Vandal resistant
- Large call button
- Call progress LED
- Integral speaker microphone
- Line powered
- Anti-tamper fixings
- Surface or flush mount

## DESCRIPTION

The disabled refuge EVC series is a range of easy to install configure and operate BS5839-9 compliant equipment designed to enable you and your clients to install BS5839-9 compliant vandal resistant disabled refuge EVC systems.

Outstation units are usually mounted in the refuge area and is used by refugees to communicate with the system operator in the event of an emergency.

The single button pro outstation is a photo luminescent green vandal resistant outstation with integral induction loop and braille annotation, suitable for use with compact and standard Folknoll Disabled Refuge EVC systems.

The unit has an integral microphone and speaker and is fitted with large vandal resistant call button and a call progress LED. The speaker and microphone volume are adjustable to suite the operating environment with a maximum audio output of 85dB for noisy areas.

The vandal resistant enclosure has a steel backed fascia and a mild steel back box with anti-tamper fixings and a surface or flush mount back box. The fascia is supplied with white photo luminescent and braille annotation alternative annotation is available on request.



### PART NUMBERS


RA7700.40	Surface mount disabled refuge EVC pro outstation
RA7700.45	Flush mount disabled refuge EVC pro outstation

### SPECIFICATIONS

Fascia:	Steel backed photo luminescent green fascia with braille and white annotation.
Mounting (surface):	Surface mount black painted mild steel back box (supplied).
Mounting (flush):	Or flush mount mild steel back box (supplied).
Dimensions:	Width: 127 mm, height: TBA mm (approx.)
Power:	Line powered
Audio output:	Adjustable up to 80 dB
Induction loop:	Fitted

### CONNECTIONS

Outstation



### DESIGNED FOR LIFE

At Folknoll all equipment is designed by experience engineers for easy installation, simple configuration, straightforward operation, low maintenance and high reliability.

### CUSTOM UNITS

Folknoll is a customer focused company. If you need special software features, custom made units or larger systems, then please contact Folknoll to discuss your requirements.

### FURTHER INFORMATION

Please contact us for further information about the wide range of Folknoll products and systems.  
Folknoll Group, Old North Rd, Royston, HERTS, SG8 5DT, UK

Tel: **+44 (0) 1763 234567**

Email: [sales@folknoll.co.uk](mailto:sales@folknoll.co.uk)

www: [www.folknoll.co.uk](http://www.folknoll.co.uk)