



RESET WHITE

Vandal resistant reset button

Steel plate

Anti-tamper fixings

Mount in 35 mm single gang back box

Suitable for stand-alone and multi-toilet systems

FOR DISABLED TOILET ALARMS

FOLKNOLL DISABLED TOILET ALARM SYSTEMS

Our disabled toilet alarm series is a range of flexible, easy to install and operate equipment, enabling you to install cost effective vandal resistant disabled toilet alarm systems. Using this range you can construct anything from stand-alone toilet alarms to site-wide systems with remote fault monitoring, events logs, graphical workstations etc.

DT7520.27 RESET WHITE

The DT7520.27 is a white painted vandal resistant disabled toilet alarm reset unit.

Reset units are installed in the toilet area to enable staff to reset activated alarms.

FOLKNOLL DISABLED TOILETS ALARMS CANNOT BE RESET REMOTELY ENSURING OPERATORS VISIT THE TOILET AREA IN RESPONSE TO AN ALARM.

The standard unit is fitted with a vandal resistant reset button. Keyed reset switches to prevent unauthorised resets can be supplied on request.

Reset buttons or keyed switches must be held for at least 0.25 seconds to reduce the risk of an accidental alarm reset.

The face plate is made from white painted mild steel and is annotated in black with the word **RESET**. Other finishes and alternative annotation are available on request.

These units can be mounted in flush or surface 35 mm single gang back boxes (not supplied).



PART NUMBERS

DT7520.27

Disabled Toilet Alarm Reset White

SPECIFICATIONS

Plate:	White painted mild steel
Mounting:	35 mm single gang back box (not supplied)
Dimensions:	Width: 86 mm, height: 86 mm, depth: < 35 mm (approx.)
Power:	12 / 24 V dc (usually supplied by battery backed system PSU)

DESIGNED FOR LIFE

At Folknoll all equipment is designed by experienced engineers for easy installation, simple configuration, straightforward operation, low maintenance and high reliability.

CUSTOM UNITS

Folknoll is a customer focused company. If you need special functionality, additional software features, customised panels or systems, please contact Folknoll to discuss your requirements.

FURTHER INFORMATION

For further information or support for any of our wide range of products, systems and services please contact **Sales at Folknoll, Old North Rd, Royston, HERTS, SG8 5DT, UK.**

Tel: **+44 (0) 1763 234567**

Email: sales@folknoll.co.uk

www: www.folknoll.co.uk