



### FEATURES

- 20m LED beacon
- Vandal resistant call button
- Can be flush or surface mounted in 35mm double gang back box (not supplied)

### DESCRIPTION

Beacon call point units combine the functions of alarm beacon, and emergency call point into a single unit.

These units are usually mounted on the wall inside a toilet to enable a user to call for assistance.

The beacon is illuminated when the alarm is activated to provide reassurance that the alarm has been activated.

The call button must be held for at least 0.25 seconds to reduce the risk of an accidental alarm reset.

The standard unit is annotated in black with the words **CALL**; alternative annotation is available on request.

These units can be mounted in double gang 35mm flush or surface mount back boxes (not supplied).



#### PART NUMBERS

DT7520.21 Beacon call point unit, stainless steel

#### SPECIFICATIONS

Fascia: Brush finished stainless steel  
Mounting: 35mm double gang back box (not supplied).  
Dimensions: Width: 86 mm, height: 86 mm Depth <35 mm (approx.)  
Power: Line powered

#### DESIGNED FOR LIFE

At Folknoll all equipment is designed by experience engineers for easy installation, simple configuration, straightforward operation, low maintenance and high reliability.

#### CUSTOM UNITS

Folknoll is a customer focused company. If you need special software features, custom made units or larger systems, then please contact Folknoll to discuss your requirements.

#### FURTHER INFORMATION

Please contact us for further information about the wide range of Folknoll products and systems.

Folknoll Group, Old North Rd, Royston, HERTS, SG8 5DT, UK

Tel: +44 (0) 1763 234567

Email: [sales@folknoll.co.uk](mailto:sales@folknoll.co.uk)

www: [www.folknoll.co.uk](http://www.folknoll.co.uk)