



VANDAL RESISTANT RESET DIALLER UNIT

BS8300:2009 COMPLIANT

Vandal resistant alarm reset unit with telephone dialler

Automatically calls operators on alarm

Allows user to talk with staff

Call button with activation delay

Reset button with activation delay

Alarm activation LED

Integral speaker and microphone

Stainless steel faceplate

Anti-tamper fixings available

Flush mount

Compatible with PABX and PSTN networks

Ideal for public places, hospitals, hotels etc.

DISABLED TOILET ALARMS

Our vandal resistant, BS8300:2009 compliant, disabled toilet alarm system provides cost-effective solutions built from standard and bespoke units. Our toilet alarms can be combined with disabled refuge EVC, fire telephone and other systems. Ideal for shops, offices, hotels and other public spaces.

RESET UNITS

Our disabled toilet alarm reset units are local alarm controllers with integral reset buttons. The units continually monitor pull cords, call points, etc. activating beacon sounders and other indicators when an alarm is triggered. The reset button is used to cancel and reset the alarm after an incident has been resolved. Reset units are usually installed inside a toilet or alarm zone to ensure alarm responders visit the location in response to an alarm.

DT7560.04 RESET DIALLER STAINLESS

The DT7560.04 Reset Dialler Stainless is a vandal resistant reset unit with built-in auto dialler and additional call button.

ILLUMINATED RESET BUTTON

The reset button resets or cancels the alarm. To reduce the risk of accidental alarm reset the button must be held for a minimum of 0.25 seconds. The button illumination mimics the action of the over-door beacon giving the user a positive visual alarm activation indication inside the toilet.

AUTO DIALLER

When an alarm is activated the built-in auto-dialler calls a pre-configured number, usually a control room or staff mobile. If the user is able to speak he/she can explain the issue to the operator. The operator is then able to arrange an appropriate response to minimize discomfort for the user.

SPECIFICATIONS

Faceplate: Stainless steel, brushed finish, black annotation
Mounting: Flush mounting in supplied back box.
Dimensions: Width: 130mm, height: 190mm (approx.)
Audio output: Adjustable

CONNECTIONS

ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We offer custom engraving, special finishes and bespoke features for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services, and find out how we can provide a solution for you.



 **Folkknoll Group Ltd.**
Old North Rd, Royston, HERTS, SG8 5DT, UK
+44 (0) 1763 234567
sales@folkknoll.co.uk www.folkknoll.co.uk