


VIDECOM OUTSTATION WITH HIGH RESOLUTION WIDE DYNAMIC RANGE COLOUR/MONO CAMERA AND DIFFUSED IR LIGHT SOURCE



IMPROVED RECOGNITION AT LOW LIGHT LEVELS

FEATURES

- Weather resistant IP65 enclosure designed for external use
- Integral speaker and microphone, high audio output (85dB)
- Large call button and progress LED
- High resolution high sensitivity super HAD II colour/mono chrome image sensor
- Diffused IR light source for close operation at low light levels
- Bright yellow die cast aluminium fascia
- Black die cast aluminium back box



DESCRIPTION

The Videcom VC-7000 series is a range of easy to install, easy to configure and easy to operate vandal resistant audio/video equipment, designed to enable you and your clients to install reliable vandal resistant video intercom systems.

The external IR video single button video outstation is a vandal resistant IP65 bright yellow and black die cast aluminium outstation specially designed for enhanced user recognition at low light levels.

The unit has an integral microphone, speaker, call button, call progress LED and high resolution high sensitivity wide dynamic range mono/colour camera with diffused IR light source.

Speaker and microphone volume are adjustable to suit the operating environment, (maximum output of 85dB for noisy areas). The camera and diffused IR light source unit are mounted in a vandal resistant dome with manual pan and tilt adjust.

STANDARD IR CAMERAS

Intercom users tend to be within an arm's length of the outstation. Standard IR cameras used at this range tend to suffer from bright highlights/glare/reflection making user recognition difficult.

FOLKNOLL DIFFUSED IR CAMERAS

The Folknoll diffused IR videcom outstation is fitted with a high resolution high sensitivity wide dynamic range camera and diffused IR light which combine to reduce close up the highlight effects and improve user recognition at low light levels.

SPECIFICATIONS

Fascia:	Aluminium, bright yellow finish, black annotation
Surface back box:	Die cast aluminium, black finish
Dimensions:	Width:130mm, Height:190mm, (approx.)
Power:	Line powered
Audio output:	Max:85dB
Video:	1 Vp-p composite, 75 Ohm PAL (colour)
Image sensor	1/3 "Sony® Super HAD II CCD
Resolution:	560 TVL
Sensor OSD features include:	TDN: true day/night switching AGC: automatic gain control Max-DR: dynamic range adjust BLC: backlight compensation DNR: digital noise reduction SENS-IP: digital sensitivity boost
Min light level	0 Lux (Close up using diffused IR)


PART NUMBERS

VC 7000-103

External surface mount, aluminium, vandal resistant diffused IR video outstation

CONNECTIONS

EXTERNAL DIFFUSED IR VIDEO OUTSTATION



Folknoll



Videcom Systems

VC 7000-103

External Diffused IR Video Outstation

VC 7700-103 DS1 V10 19/01/2011 Videcom Systems External Diffused IR Video Outstation

DESIGNED FOR LIFE

At Folknoll all equipment is designed by experience engineers for ease of installation commissioning and operation.

CUSTOM UNITS

Folknoll is a customer focused company. If you need special software features, custom made units or larger systems, then please contact Folknoll to discuss your requirements.

FURTHER INFORMATION

Please contact us for further information about the wide range of Folknoll products and systems.

Folknoll Group, Old North Rd, Royston, HERTS, SG8 5DT, UK

Tel: +44 (0) 1763 234567

Email: sales@folknoll.co.uk

www: www.folknoll.co.uk