

Door Entry Systems DE4501.20

Extra Tough Vandal Resistant Intercom

DE 6000-034 DS1 V100 21/01/2015 Door Entry Systems Extra Tough Vandal Resistant Intercom

EXTRA TOUGH VANDAL RESISTANT INTERCOM



FOR DOOR ENTRY SYSTEMS

FEATURES

- Extra tough, vandal resistant, 2.5 mm, stainless steel plate
- IP65, weather resistant assembly with neoprene gasket seal
- Suitable for use with super flush back box (shown above)
- Can be sunk into anti-pick adhesive (when used with super flush back box)
- Vandal resistant call button and LED
- Anti-tamper fixings

DE4501.20 EXTRA TOUGH INTERCOM

Our DE4501.20 door entry intercom unit is designed for extra tough locations. The front plate is made from 2.5 mm stainless steel, and is fitted a vandal resistant call button and LED.

The unit can be mounted in our super flush back box to form a weather resistant IP65 assembly.

For extra security the super flush back box has a 15 mm bezel, allowing the assembly to be sunk into anti-pick adhesive whilst still allowing access for maintenance.

IDEAL FOR OUTDOOR PUBLIC PLACES AND EXTRA TOUGH LOCATIONS



Door Entry Systems DE4501.20

Extra Tough Vandal Resistant Intercom

DE 6000-034 DS1 V100 21/01/2015 Door Entry Systems Extra Tough Vandal Resistant Intercom

SPECIFICATIONS

Plate:	2.5 mm stainless steel
Dimensions:	Height: 200 mm, width: 140 mm, depth: 65 mm (approx.)
Ingress protection:	IP 65
(When used with DE4501.32)	

PART NUMBERS

DE4501.20
DE4501.32

Extra tough vandal resistant intercom Super flush back box

DESIGNED FOR LIFE

At Folknoll all equipment is designed by experienced engineers for ease of installation, commissioning and operation.

CUSTOM UNITS

Folknoll is a customer focused company. If you need special software features, custom made units or larger systems, then please contact Folknoll to discuss your requirements.

FURTHER INFORMATION

Please contact us for further information about the wide range of Folknoll products and systems.Folknoll Group, Old North Rd, Royston, HERTS, SG8 5DT, UKTel: +44 (0) 1763 234567Email: sales@folknoll.co.ukwww.folknoll.co.uk