



BRIGHT RED BS 5839-9 COMPATIBLE FIRE TELEPHONE

Integral speaker for hands-free operation

Handset for telephone operation
(automatically activated when door opened)

Internal call button, call progress LED and microphone

Adjustable audio output (up to 80dB)

Line powered

Compatible with standard, compact and combined EVCS systems

High quality, vandal-resistant, steel case

Surface or flush mount

Designed for public places

DISABLED REFUGE EVCS

Folknoll's vandal resistant, **BS 5839-9** compatible, disabled refuge EVCS offers vandal resistant solutions for **MUSEUMS, RAILWAY STATIONS, HOTELS** and other **PUBLIC SPACES**. Our great range of outstations, master stations and control equipment, enables us to construct systems to suit your requirements. All of our products can be customised with photoluminescent, Braille, tactile and multilingual annotation. We can even combine our disabled refuge EVCS with fire telephones, emergency assistance and other building alarms to provide **COST-EFFECTIVE** solutions for smaller sites.

FIRE TELEPHONES

Our EVCS fire telephone outstations can be added to compact, standard or combined Folknoll disabled refuge EVCS to provide BS 5839-9 compliant combined disabled refuge/fire telephone/emergency assistance alarm systems. Saving control room space, simplifying installation and reducing cabling requirements.

RA7700.50/55: FIRE TELEPHONE

The RA7700.50/55 Fire Telephone has a red handset for fire telephone operation and an integral speaker for hands free operation. The unit automatically switches from hands free to telephone operation when the door is opened. The fire telephone outstation can be called from the disabled refuge master station allowing operators to attract attention and make announcements. Speaker volume and microphone gain are independently adjustable to suit the operating environment, with a maximum output of 80dB for noisy areas.

MOUNTING

The unit is supplied in a bright red, mild steel, surface or flush mount enclosure with anti-tamper fixings.

POWER

This unit is usually line powered from a standard system controller or a compact system master panel.

APPLICATION

This outstation is suitable for use with standard, compact and combined Folknoll Disabled Refuge EVCS systems.

SPECIFICATIONS

Enclosure:	Bright red, mild steel enclosure with white symbols and annotation
LED:	Red call progress indicator LED
Audio output:	Adjustable (max: 80dB)
Power:	24Vdc (usually line powered)

ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We also offer individual annotation, custom engraving and special finishes for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services and find out how we can provide a solution for you.



19 Old North Rd, Royston, HERTS, SG8 5DT, UK

Folknoll Group Ltd

www.folknoll.co.uk

+44 (0) 1763 234567

enquiries@folknoll.co.uk