EMERGENCY ASSISTANCE ALARMS



IP65 ABS PULL CORD UNIT

3000mm cord with 2 pull handles for high-level and low-level activation

Can be daisy-chained for multiple alarm activation points

Robust, water resistant, ABS construction

Surface mount in supplied back box, hidden fixings

Ideal for wet public places, bathrooms, showers, etc.

EMERGENCY ASSISTANCE ALARMS

Folknoll emergency assistance alarm systems offer cost-effective, vandal resistant, **BS 8300-2** and **DOCUMENT M** compatible solutions built from standard and bespoke units. Our alarms can be combined with disabled refuge EVCS and other systems. Ideal for **SHOPS**, **OFFICES**, **HOTELS** and other **PUBLIC SPACES**.

PULL CORD UNITS

Pull cords, alarm strips and call points are used to call for assistance in emergency. The units are mounted in strategic locations in accordance with current standards, enabling distressed persons to activate alarms. Depending on the system configuration, beacons, sounders and remote monitoring units will alert staff on activation.

DT7520.86: PULL CORD, IP65, ABS

Our DT7520.86 Pull Cord, IP65, ABS is a tough water-resistant, alarm pull cord unit.

PULL CORD HANDLES

This unit is usually supplied with 3000mm cord and two pull handles offering high-level and low-level activation points. The handles can be positioned anywhere along the cord to comply with local regulations, specifications and requirements. Alternative cord lengths and additional pull handles are available on request.

FACEPLATE / ENCLOSURE

This face plate and supplied back box is made from light grey ABS, which forms a surface mounting, water-resistant IP65 enclosure with hidden fixings when assembled.

MOUNTING

This unit is designed to be ceiling mounted, care should be taken to ensure cable entry is properly sealed to maintain the IP65 rating.

DT7520.86: PULL CORD, IP65, ABS

EMERGENCY ASSISTANCE ALARMS

SPECIFICATIONS

Pull cord: 3000mm cord with 2 pull handles for high-level and low-level activation

Enclosure: ABS(UL 94 HB), light grey(RAL 7035) construction

Ingress Protection: IP65

Mounting: Surface mount, with hidden fixings

Dimensions: Width: 80mm, height: 80mm, depth: 60mm (approx.)

Power: 12Vdc / 24Vdc, usually supplied from battery backed system PSU

ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We also offer individual annotation, custom engraving and special finishes for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services and find out how we can provide a solution for you.



+44 (0) 1763 234567

enquiries@folknoll.co.uk