

NC7604: PULL CORD ABS NURSE CALL SYSTEMS



ABS PULL CORD ALARM ACTIVATOR

3000mm cord 2 pull handles for high-level and low-level activation Reassurance LED - indicates alarm status Can be daisy chained for multiple alarm activation points Tough ABS construction Anti-tamper fixings available Surface mount - fits round conduit box / BESA box Ideal for public places, hospitals, hotels, etc. Compatible with Folknoll remote monitoring

NURSE CALL SYSTEMS

Nurse call systems enable residents, visitors and staff to call for assistance in the event of emergency or other contingency.

FOLKNOLL WILL DESIGN AND SUPPLY FULLY TESTED SYSTEMS OR INDIVIDUAL COMPONENTS. PLEASE CONTACT OUR TEAM OF ENGINEERS TO DISCUSS YOUR REQUIREMENTS.

PULL CORD UNITS

Pull cords, alarm strips and call points are used to call for assistance in emergency. The units are mounted in strategic locations in accordance with current standards, enabling distressed persons to activate alarms. Depending on the system configuration, beacons, sounders and remote monitoring units will be used to alert staff and others to respond to incidents.

NC7604: PULL CORD ABS

Our NC7604 Pull Cord ABS is a tough ABS, BESA, ceiling mount, alarm pull cord unit with reassurance LED.

PULL CORD HANDLES

The unit is usually supplied with 3000mm cord and two pull handles, offering high-level and low-level activation points. The handles can be located anywhere along the cord to comply with local regulations, specifications and requirements. Alternative cord lengths and additional pull handles are available on request.

REASSURANCE LED

The reassurance LED indicates the state of the local emergency alarm. The exact behaviour of this LED depends on the type of alarm control system used. Typically, the LED flashes in the alarm activated state and is illuminated continuously in the alarm acknowledged state.

FACEPLATE / ENCLOSURE

The pull cord is supplied in a tough, surface mount, ABS cover. Alternative enclosures are available on request.


MOUNTING

The unit designed to be surface mounted on a suitable ceiling or fitted to a standard round conduit / BESA box (not supplied).

SPECIFICATIONS

Pull cord:	3000mm cord with 2 pull handles for high-level and low-level activation
Indicator:	Red reassurance LED, indicates alarm status
Faceplate /	ABS cover, white finish
Enclosure:	
Mounting:	Surface mount, fits round conduit / BESA box
Dimensions:	Diameter: 78mm, depth: 40mm (approx.)
Power:	12Vdc / 24Vdc, usually supplied from battery backed system PSU

CONNECTIONS



ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We also offer individual annotation, custom engraving and special finishes for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services and find out how we can provide a solution for you.



+44 (0) 1763 234567

enquiries@folknoll.co.uk